



# Walhachin

---

## FIRESMART COMMUNITY ASSESSMENT REPORT

Prepared for  
Thompson Nicola Regional District

October 2019

Brittany Seibert, LFR

Frontline Operations Group, Ltd. | 11510 UPPER SUMMIT DRIVE, COLDSTREAM BC V1B 2B4

## Summary of Recommendations – Abbreviated

The FireSmart program provides detailed guidelines and recommendations to reduce home ignition potential during a wildfire. The recommendations made in this report must be considered *in addition* to those contained in the FireSmart *Protecting Your Community from Wildfire* manual. The following summary of recommendations is taken from Section 7 of this report, where additional detail and rationale is provided. These recommendations are specific for the community of Walhachin but can be applied to communities with similar characteristics.

### Recommendations for Walhachin

1. Reduce the amount of highly combustible plants used in landscaping, such as cedar and juniper shrubs and hedges within Zone 1 (<10m from the home). Refer to the *FireSmart Landscaping Guide* for recommended vegetation and landscaping materials
2. Remove or store appropriately all combustibles in Zone 1 – including personal items such as trailers, recreational vehicles, tools, building materials, etc.
3. Apply FireSmart principles to any outbuilding within 15m of a structure
4. Zone 2 (10-30m) and Zone 3 (30-100m) can reduce grass and shrub fuel loading through mitigations such as burning, grass trimmers and livestock grazing.
5. Fuels located on crown land within 100m of a resident's home should be assessed by a qualified professional to determine next course of action
6. Remove firewood stacks from Zone 1 during times of wildfire threat
7. When away for lengths of time during high wildfire threat, consider items such as rattan door mats, flammable patio furniture, children's toys, trash cans, BBQs, etc. as combustibles and store away
8. Create a local FireSmart Board and Community Plan to maintain awareness and community participation

Table of Contents

**Summary of Recommendations – Abbreviated .....2**

**List of Figures .....4**

**1.0 Introduction .....5**

**2.0 Definition of Ignition Zone .....6**

**3.0 Description of the Fire Environment.....7**

**3.1 Fuels .....7**

        3.1.1 Fuel Layers..... 7

        3.1.2 Fuel Size ..... 8

**3.2 Weather .....9**

        3.2.1 Wind ..... 9

        3.2.2 Temperature and Relative Humidity ..... 9

        3.2.3 Precipitation ..... 10

**3.3 Topography .....10**

**4.0 Site Description ..... 11**

**4.1 Fuel Type ..... 11**

        4.1.1 O1 Fuel Type\* ..... 11

**4.3 Topography .....12**

**4.4 Human Ignition Potential .....13**

**5.0 Assessment Process..... 13**

**6.0 Observations and Issues ..... 13**

    6.1 Roof Assemblies .....14

    6.2 Building Exteriors.....14

    6.3 Nearby Combustibles.....15

    6.4 Vegetation.....15

**7.0 Recommendations ..... 16**

**8.0 Successful FireSmart Mitigations ..... 17**

    8.1 Fire-Resistant Roofing.....18

    8.2 Landscaping.....18

**9.0 Next Steps..... 19**

**10.0 Signature of Local FireSmart Representative .....20**

**APPENDIX 1: Resources.....21**

**APPENDIX 2: Community Wildfire Hazard Assessment form..... 1**

## List of Figures

Figure 1 Walhachin community .....	5
Figure 2 FireSmart Canada utilizes the concept of priority zones surrounding a home to help residents prioritize their hazard reduction efforts. A home’s immediate surroundings (Zones 1 and 1a) are of immediate concern to the homeowner and should be targeted aggressively to reduce ignition hazards to the home.....	7
Figure 3 Wildland fuels can be described within three broad fuel layers: Ground fuels, surface fuels (to a height of 2m above the duff layer), and canopy fuels. Canopy fuels are also referred to as aerial fuels ....	8
Figure 4 shows the relationship between temperature and relative humidity, as temperatures increase and the overall water content in the air does not change, relative humidity decreases. This affects fire behavior through the increased drying of fuels .....	10
Figure 5 Walchin community is surrounded primarily by O1 fuel type. To the immediate west, however, there is agricultural fields that can still be consider O1 but will likely demonstrate different fire behavior depending on time of season (i.e. green and growing vs. cut and curing). .....	12
Figure 6 Satellite imagery of Walhachin .....	12
Figure 7 Contour map of Walhachin.....	13
Figure 8 The roof is one of the most important aspects to the home that can reduce the probability of ignition during a wildfire event. Aging roofs pose a risk to home ignition because of exposures to more readily ignitable materials. ....	14
Figure 9 Combustibles such as firewood, building materials, trailers, ATVs, etc. should all be stored 10m away from the home. ....	15
Figure 10 Conifers, and Cedar and Juniper hedges and shrubs should be removed from Zone 1 (0-10m). These species are more easily ignitable and offer easy access to ladder fuels – resulting in increased fire behavior and radiant heat. These plants should be replaced by leafy, deciduous plants which are much more resilient to ignition. ....	16
Figure 11 Fire-rated roofing material is proven to be highly resilient against home ignition during a wildfire event. Roof design can also contribute to mitigation of debris accumulation by minimizing valleys and pinch point where debris can be captured.....	18
Figure 12 This home demonstrates several FireSmart landscaping attributes. The gravel provides a non-combustible surface creating a break from direct flame contact to the home. Conifers have been removed up to 10m away and ladder fuels have been cleared. Leafy, deciduous plants are the preferred vegetation to be found in zone 1.....	19

## 1.0 Introduction

The FireSmart approach is designed to provide an effective management approach for preserving wildland living aesthetics while reducing community ignition potential during a wildland urban interface (WUI) fire. The program can be tailored for the adoption by any community and/or neighborhood association that is committed to ensuring its citizens maximum preparation for wildland fire. The following Community Assessment Report (CAR) is intended to be a resource for residents of Walhachin for carrying out the recommendations and actions.

The CAR was developed by a trained Local FireSmart Representative (LFR). This assessment addresses the wildfire-related characteristics of Walhachin. It examines the area's exposure to wildfire as it relates to ignition potential. The assessment does not focus on the specific homes, but examines the community as a whole.

Funding for the Thompson Nicola Regional District – Walhachin – FireSmart project was provided through the Community Resiliency Investment program and was provided by the Union of BC Municipalities. The grant enabled the regional district to retain the services of Frontline Operations Group to conduct the project.

Community assessment was carried out on September 11, 2019 by Brittany Seibert, LFR.




Figure 1 Walhachin community

## 2.0 Definition of Ignition Zone

Walhachin is located in a wildfire environment. The wildland areas surrounding the community are typical ecosystems that have developed, historically, from frequent low intensity fires. With the introduction of modern forest protection policies, the typical fire cycle has been interrupted thus contributing to a host of cascading ecological effects including the buildup of forest fuels.

Wildfires will happen in the Thompson Nicola region – exclusion from wildfire is not a choice. In 2017 the province of British Columbia was subjected to one of the worst fire seasons in its history. Over 1.2 million hectares were burnt and roughly 65,000 residents were evacuated. The Thompson Nicola region alone saw one of the most devastating fires of that year, Elephant Hill. The fire discovered on July 6, 2017 continued to burn for another 76 days and consumed over 190,000 hectares. Over the course of the fire, over 120 homes were destroyed.

A house burns because of its relationship with everything in its surrounding home ignition. To avoid a home ignition, a homeowner must eliminate the wildfire's potential relationship with their house. This can be accomplished by interrupting the natural path a fire takes by clearing fuel from the home ignition. To accomplish this, flammable items such as excessive vegetation and flammable debris must be removed from the areas surrounding the structure. This will prevent ignition of fuel sources in proximity of the structure and prevent direct contact of flames with the home. Reducing the volume of fuels and reducing its ability to move vertically will affect the intensity of the wildfire as it nears the home.

Included in this assessment are observations made while visiting Walhachin. The assessment addresses the ease with which home ignitions can occur under severe wildfire conditions and how these ignitions might be avoided within the home ignition zones of affected residents. Walhachin residents can reduce the risk of structure loss during a wildfire by taking actions within their home ignition zones – which includes a house and its immediate surroundings within 100 metres (figure 2). Given the extent of these zones, the ignition zones of several homes sometimes overlap, and often spill over onto adjacent public or community land.

The results of the assessment indicate that wildfire behavior and subsequent losses will be dominated by the residential characteristics of this area. The good news is that residents will be able to substantially reduce their exposure to loss by addressing community vulnerabilities. Relatively small investments of time and effort will reap great rewards in wildfire safety.



Figure 2 FireSmart Canada utilizes the concept of priority zones surrounding a home to help residents prioritize their hazard reduction efforts. A home’s immediate surroundings (Zones 1 and 1a) are of immediate concern to the homeowner and should be targeted aggressively to reduce ignition hazards to the home.

### 3.0 Description of the Fire Environment

Wildland fire behavior is influenced by the interaction of three broad environmental factors: fuel, weather and topography. Collectively these factors describe the fire environment and determine the intensity and rate of spread of a wildland fire. A working knowledge of the factors that characterize the fire environment is helpful for building an awareness of hazard mitigation at the site level.

#### 3.1 Fuels

In the context of wildland fire, fuel refers to the organic matter involved in combustion. In Canada, wildland fuels are classified into 16 fuel types within the Canadian Forest Fire Behavior Prediction (FBP) System. The FBP system is informed by the Canadian Forest Fire Danger Rating System (CFFDRS), which is the primary tool to obtain predictive wildfire management intelligence used by agencies across Canada.

When dealing with the wildland-interface environment fuel can extend beyond the surrounding vegetation. Fuels can include a structure’s composition, neighboring buildings, vehicles and other combustible materials found around the home – see section 6.3

##### 3.1.1 Fuel Layers

The structure and arrangement of fuels are described in terms of their horizontal and vertical continuity within three broad layers of the fuel complex – ground fuels, surface fuels and canopy (or aerial) fuels (Figure 3). Ground fuels occupy the *duff layer* and the uppermost portions of the soil mineral horizon. In general terms, the duff layer is comprised of decomposing organic material and is found beneath the litter layer and above the uppermost soil mineral horizon (A-horizon). The components of the duff layer

lack identifiable form due to decomposition (as opposed to the *litter layer*, which is composed of identifiable material).

The surface fuel layer begins above the duff layer and extends 2m vertically. Surface fuels are characterized by the litter layer (leaves, needles, twigs, cones, etc.) as well as plants and dead woody material up to a height of 2m. In some cases, surface fuels may act as *ladder fuels* that can carry fire from the surface fuel layer into the canopy layer.

Canopy fuels are the portions of shrubs and trees that extend from 2m above the duff layer, upwards to the top of the fuel complex. Certain tree species, such as several spruce species (*Picea* sp.) are characterized by branches extending down to the forest floor, whereby these lower branches act as ladder fuels. Other species, particularly those found in drier, fire-maintained ecosystems, such as Ponderosa pine, lack these ladder fuels and form a distinct separation between the surface fuel layer and canopy fuel layer.




Figure 3 Wildland fuels can be described within three broad fuel layers: Ground fuels, surface fuels (to a height of 2m above the duff layer), and canopy fuels. Canopy fuels are also referred to as aerial fuels

### 3.1.2 Fuel Size

Wildland fuel can be further described in terms of relative size – so called *fine fuels* and *coarse* or heavy fuels. Fine fuels include leaves and conifer needles, grasses, herbs, bark flakes, lichen, twigs etc. Large branches, downed logs and other large woody material are considered coarse or heavy fuels. Fine fuels have a higher surface area to volume ratio than coarse fuels, and this characteristic influences the rate of drying and ease of ignition.

With a higher surface area to volume ratio than coarse fuels, fine fuels are more readily influenced by changes in environmental conditions (e.g. relative humidity, wind, precipitation etc.). As well, dead fine fuels react to changes in environmental conditions at a relatively faster rate than green (i.e. live) fine

fuels.

When available to burn, fine fuels ignite more easily and spread fire faster than coarser fuels. This characteristic makes fine fuels particularly susceptible to ignition from firebrands (or embers). Additionally, fine fuels are more susceptible to becoming firebrands – mobile ignition sources – as they are lighter and more easily made airborne. Finally, fine fuels take a shorter time to burn out than coarser fuels.

For any given fuel, the more there is and the more continuous it is, the higher the intensity of the fire will be and the faster the fire will spread.

### 3.2 Weather

Weather condition affect the moisture content of wildland fuels and influence the rate of spread and intensity of a wildland fire. Weather is the most dynamic element of the fire environment and the most challenging to assess and forecast. There are four main components of weather to consider when discussing wildland fire behavior: wind, temperature, relative humidity and precipitation.

#### 3.2.1 Wind

Wind speed and direction influences the rate and direction of spread of a wildland fire. The application of wind on open flame has the effect of tilting the flame away from the wind, and, in the case of wildland fire, placing the flame into closer proximity (or contact) with downwind fuels thus contributing to fire spread.

Wind can also contribute to a preheating effect on fuel immediately downwind from open flame. Wind hastens the drying process of exposed fuel, with the rate of drying being a function of the surface to volume ratio. Having a relatively higher surface area to volume ratio, fine fuel moisture content is affected to a greater degree by wind when compared to coarse fuel.

Lastly, wind can also influence the ignition of a new wildland fire through its contribution to spotting. Ignited fine fuels – that have become airborne through rising thermal air – can be carried by wind over the course of large distances. These firebrands result in the ignition of new fuels cultivating in new fires.

#### 3.2.2 Temperature and Relative Humidity

Temperature and relative humidity have a close and inverse relationship – as temperature increases, relative humidity decreases. This is because relative humidity is the percent of water vapor in the air compared to what would be present if it were saturated. As air is heated through increasing temperatures, its ability to hold more moisture also increases. However, without the introduction of more moisture the percentage decreases.

$$rH = \frac{\text{Amount of moisture currently in the air} \times 100}{\text{Amount of moisture air can hold}}$$

The moisture content of wildland fuel is constantly seeking to equalize with moisture content of the surrounding air. This effect is most pronounced in dead fuel. When the relative humidity is high, dead

fine fuels will readily absorb moisture from the air and conversely, when the relative humidity is low, dead fine fuels will readily give up moisture to the air.




Figure 4 shows the relationship between temperature and relative humidity, as temperatures increase and the overall water content in the air does not change, relative humidity decreases. This affects fire behavior through the increased drying of fuels

### 3.2.3 Precipitation

The effect of moisture on wildland fuel is dependent on the size and state of the fuel. The moisture content of dead fine fuel is highly reactive to changes in relative humidity, precipitation and wind. Fine fuels require less precipitation to reach saturation than coarse fuels, and in turn, dry out at a faster rate.

Precipitation's arrival in the form of thunderstorms can inadvertently increase fire behavior, even if for short time. Thunderstorms can generate large influxes in wind through in and out flows, and downdrafts which have adverse effects on fire behavior.

### 3.3 Topography

In the context of the fire environment, topography refers to the shape and features of the landscape. Of all the topography factors in fire behavior, the primary importance for an understanding of fire behavior is slope. When all other factors are equal, a fire will spread faster up a slope than it would across flat ground. When a fire burns on a slope, the upslope fuel particles are closer to the flame compared to the downslope fuels. This pre-heating effect on upslope fuels contributes to fast upslope fire spread. As well, hot air rising along the slope tilts the flame uphill which further increasing the ease of ignition of upslope fuels.

Topography influences fire behavior principally by the steepness of the slope. However, the configuration of the terrain such as narrow draws, saddles and so forth can also influence fire spread and intensity. Slope aspect (i.e. the cardinal direction that a slope faces) determines the amount and quality of solar radiation that a slope will receive, which in turn influences plant growing conditions and drying rates.

## 4.0 Site Description

Walhachin is located approximately 60km west of Kamloops, BC on the south side of the Thompson River. It is neighbored by Thompson Rivers Estates community which is located directly north, on the northern edge of the Thompson River.

There are ~25 homes with additional outbuildings on private properties, and at least one community building. The community is accessed from the Trans-Canada Highway (HWY 1) from Riverview Dr./Walhachin Station Rd. There appears to only be one vehicle bridge crossing in the area. Local knowledge may provide other access and egress options for the community. Roads within the community are looped back to Walhachin Station Rd.

All structures feature a variety of ember accumulator features such as complex roof shapes, deck configurations and open (unsheathed) deck constructions and open carports. All structures feature a high degree of vulnerability to ignition of structures and Priority Zone 1 combustibles by wind driven embers. Lots are of varying sizes but mostly standard size and configuration with homes separated from each other by 10-20m. Some natural vegetation on the properties has been retained with significant additions of planted trees, hedges and ornamental plants.

### 4.1 Fuel Type

Classifying fuel complexes in BC according to the FBP fuel types is an imperfect process, given the diversity of ecosystems in the province in comparison to the rest of Canada. When considering FBP fuel types for a particular fuel complex, the actual species composition is of less importance than the overall stand structure characteristics. The FBP fuel types referenced below specify. Certain species not found in BC (e.g. red pine and eastern white pine, etc.), however the overall structural characteristics of the fuel types share similarities with the Walhachin site conditions. Herein lies the challenge of classifying certain BC forest types into a handful of FBP fuel types. In the Walhachin area, the community's perimeter (up to 100m) contains primarily O1 (open grass). The perimeter includes both private and public land.

#### 4.1.1 O1 Fuel Type\*

The O1 fuel type is characterized by continuous grass cover, with no more than occasional trees or shrub clumps that do not appreciably affect fire behavior. Two subtype designations are available for grasslands; one for the matted grass condition common after snowmelt or in the spring (O1-a) and the other for standing dead grass common in late summer to early fall (O1-b). The proportion of cured or dead material in grasslands has a pronounced effect on fire spread there and must be estimated with care.

*\*Excerpt taken from the CFFDRs FBP*




*Figure 5 Walchin community is surrounded primarily by O1 fuel type. To the immediate west, however, there is agricultural fields that can still be consider O1 but will likely demonstrate different fire behavior depending on time of season (i.e. green and growing vs. cut and curing).*

## 4.2 Fire Weather

The climatic conditions of the southern and central region of the Thompson-Nicola can be broadly characterized by warm, dry summers and cool winters. The Walhachin community lies in the center of British Columbia’s dry belt and receives on average less than 20cm of rain a year.

## 4.3 Topography

Walhachin is located above the Thompson River on a natural bench. A gradual slope rises to the south of the community leading to another bench/plateau. The slope below the community is likely to increase fire intensities as the fire front approaches. However, the community is set back from the slope and has a fuel break – a paved road – between the homes and the slopes edge. Therefore, fire intensities would diminish as it crests the hill and into the community. Fuel type and weather likely to play a bigger role in fire behavior.



*Figure 6 Satellite imagery of Walhachin*




Figure 7 Contour map of Walhachin

#### 4.4 Human Ignition Potential

There are several opportunities for human caused ignitions. Burning on private land – including campfires or burn piles – that are poorly managed or extinguished has the potential to escape and ignition nearby fuel sources or vegetation. As well, a railway pass through the community directly to the south. It is not uncommon for sparks to be thrown by passing railcars into nearby vegetation resulting in a wildfire ignition.

#### 5.0 Assessment Process

The Walhachin community was assessed by Local FireSmart Representative, Brittany Seibert, during her visit on August 7, 2019. The community and adjacent vegetation within a least a 100m radius was assessed and observations were recorded using the *FCCRP Community Hazard Assessment Form* (see Appendix 2). The assessment process noted a number of attributes that contribute both negatively and positively towards the risk of property damage/loss due to a wildfire event.

As part of the FireSmart project – funded by the TNRD – a FireSmart public talk was given on the same day at a local resident’s house in the Walhachin community. The objective of the talk was to educate home owners on the use of the *FireSmart Site and Structure Hazard Assessment Form* to help identify and prioritize hazards as they relate to wildland fire and their homes. The invitation was open to all members of the community – including Thompson Rivers Estates – and was advertised through the TRND’s Facebook page. There were 6 residents in attendance.

#### 6.0 Observations and Issues

The following observations were noted during the community wildfire hazard assessment. See Appendix 2 to view the entire community wildfire hazard assessment form and notations.

## 6.1 Roof Assemblies

A home's roof is the largest surface most that is the exposed to embers during a wildfire. Homes with a flammable wood shake roof have a much higher probability of igniting during a wildfire compared to a non-wood roofing system. Homes in the Walhachin community were seen to have fire-rate roofing materials.

Majority of the roofs seen appeared to have no accumulation of combustible debris. Clean roofs will mitigate the potential of burning debris that may challenge a roof's fire resistance and reduce the chance of igniting another fuel source. There were however, some roofs seen in variable conditions. As roofs age the materials begin to curl, peel and breakdown leading to exposure of the combustible wood underside. Organic material, such as moss, may be growing and can pose a risk to home ignition. It is important for roofs to remain free and clear of combustible debris.



*Figure 8 The roof is one of the most important aspects to the home that can reduce the probability of ignition during a wildfire event. Aging roofs pose a risk to home ignition because of exposures to more readily ignitable materials.*

## 6.2 Building Exteriors

Risk factors associated with the exterior surface of a structure are less dependent on the characteristics of the exterior cladding system (e.g. stucco vs. cement board vs. vinyl siding etc.) and more dependent on the likelihood of direct flame contact and/or ember accumulation on the structure. Accumulated fuel along an exterior wall can negate the fire-resistant advantages that any particular exterior cladding system provides, should the fuel ignite. The removal of fuel accumulations along any exterior wall should be of much greater concern than the actual composition of the wall itself.

### 6.3 Nearby Combustibles

In the context of the structure and site hazard assessment, *nearby combustibles* refer to non-vegetative fuel, such as firewood, wood fences, sheds, vehicles etc. Outbuildings are of particular concern if they are located within 15m (45ft) of the home. Outbuildings pose a threat to the ignition of a home because they are able to sustain extreme radiant heat for over long periods of time. There is an additional risk of firebrand production which poses a risk to any nearby structures or fuel sources. Any outbuilding that is located within 15m (45ft) should have FireSmart principles applied to mitigate potential ignition.

Firewood is a serious risk as it will easily ignite during a wildfire event and burn intensely once lit. Often firewood is located near the principal building and is often responsible for igniting interface buildings during a wildfire. It is recommended that firewood be stack a min. 10m away from the home during the wildfire season. A pre-caution to shoulder months as wildfire seasons has shown signs in recent years of burning earlier and later through the calendar year. Items such as RVs, trailers, vehicles etc. are often not view as a combustible. However, these items do have the potential to ignite and as a result pose a some threat when stored within 10m of the home.



Figure 9 Combustibles such as firewood, building materials, trailers, ATVs, etc. should all be stored 10m away from the home.

Direct flame contact is often thought of as the primary factor in home ignition and subsequent loss. However, recently it has become more apparent that ignition from a firebrand is the most likely scenario. Because of this, innocuous items commonly found around the outside of a home may act as combustibles that could ignite the home. Flammable patio furniture (particularly seat cushions), sisal doormats and rats, or even a corn broom leaning against the house are all potential fuels that could ignite from ember accumulation.

### 6.4 Vegetation

Vegetation is assessed in three concentric zones around a home (Figure 2), with Priority Zone 1 (PZ-1) being the area occupying the first 10m (30ft) around the structure. More recently Zone 1a (PZ-1a), known as the *non-combustible zone*, has been added to distinguish the importance of the first 1.5m (4.5ft) from a structure. The quantity and condition of canopy, ladder and surface fuels are the key factors assessed in regards to vegetation.

## WALHACHIN FIRESMART COMMUNITY ASSESSMENT REPORT

In Walhachin community the main fuel source is open grass and sage brush. There appears to be no native tree species within 100m of the community. There were, however, several planted species were seen within the community – particularly in PZ-1(a). These included various deciduous, conifers, and cedar and juniper shrubs and hedges. Deciduous species are the recommended vegetation to be planted within the PZ-1(a) as they are naturally resistive to intense wildland fire behavior. This is because the species lacks the ladder fuels for vertical fire growth, maintains a higher moisture content within its leaves, and has smooth, tight bark that makes it difficult for fire to climb.

Conifer species pose a significant risk when found within the PZ-1(a). They offer easily accessible ladder fuels for wildland fire to reach the canopy and create large amounts of needle litter sustaining surface fire. Cedar and Juniper shrubs and hedges are also problematic from a home ignition perspective. These species are rich in organic volatile compounds and terpenes making them easily ignitable.



*Figure 10 Conifers, and Cedar and Juniper hedges and shrubs should be removed from Zone 1 (0-10m). These species are more easily ignitable and offer easy access to ladder fuels – resulting in increased fire behavior and radiant heat. These plants should be replaced by leafy, deciduous plants which are much more resilient to ignition.*

Most homes in the Walhachin community have overlapping zones. In many cases, one home's PZ-1 is the adjacent home's PZ-1. This is a common characteristic of higher-density WUI areas and it reinforces the view that many individual FireSmart efforts can increase the overall wildfire resilience of the entire neighborhood. Unfortunately, the same holds true when one (or more) homes aren't FireSmart and pose a threat to adjacent homes that are.

### 7.0 Recommendations

FireSmart seeks to create a sustainable balance that will allow communities to live safely while maintaining environmental harmony in a wildland urban interface (WUI) setting. Homeowners already balance their decisions about fire protection measures against their desire for certain flammable components on the properties. It is important for them to understand the implications of the choices they're making. These traces directly relate to the ignitability of their home ignition zones during a wildfire.

A home owner/community must focus attention on the home and surrounding area and eliminate the fires potential relationship with the house. This can be accomplished by disconnecting the house from

## WALHACHIN FIRESMART COMMUNITY ASSESSMENT REPORT

high and/or low-intensity fire that could occur around it, and by being conscious of the devastating effects of wind driven embers.

The following section of this report provides recommendations for consideration by the Walhachin community concerning wildfire safety issues that were identified as priorities during the assessment:

- Removal of conifers and combustible plants within the Non-Combustible (0-1.5m) and Zone 1 (1.5-10m) will significantly reduce the fire hazard rating for structures and properties within the community. Refer to the *FireSmart Landscaping Guide* for recommended plants for these zones.
- Personal items such as trailers/RVs, recreational vehicles, tools, building materials, etc. are all considered combustible and should be stored appropriately or removed from zone 1 (>10m from home).
- Neighboring buildings such as sheds or detached garages located within 15m of the home should also be considered as a fuel source. It is recommended that they also have FireSmart mitigations done to and around them to prevent ignition.
- Treatment of fuel loading Zone 2 (10-30m) and Zone 3 (30-100m) can be managed through spring burning and summer vegetation trimming or livestock grazing.
  - Priority zones (up to 100m from a home) that fall onto crown land should be assessed by a qualified profession to determine the next course of action.
- Homes with firewood stacks are reminded during wildfire season to have wood stacked a min. of 10m away from the structure. Firewood may be moved closer to the home during times of low wildfire threat (i.e. winter). Homeowners should be aware that wildfire seasons have demonstrated early and late burning periods in a calendar year. Therefore, homeowners should remain vigilant during should seasons to changing weather conditions.
- When fire weather is severe and the home is unoccupied, homeowners should remember not to leave flammable items outside. This includes rattan doormats, flammable patio furniture, children's toys and trash cans.

It is recommended that the community come together to create FireSmart Community Plan regardless of the community's intention to seek FireSmart Community Recognition status. A FireSmart Community Plan is generally a simple action plan, comprised of at least three agreed-upon, doable action items that will improve a community's wildfire readiness. The Community Plan can be modified with the passage of time and renewed with each new wildfire season.

### 8.0 Successful FireSmart Mitigations

When adequately prepared, a house can likely withstand a wildfire without the intervention of the fire service. Further, a house and its surrounding community can be both FireSmart and compatible with the area's ecosystem. The FireSmart Communities program is designed to enable communities to achieve a high level of protection against wildfire loss even as a sustainable ecosystem balance is maintained.

Other than the replacement of an unrated wood roof or replacing a flammable deck, most FireSmart hazard mitigations around the home are inexpensive and straightforward. In many ways, hazard mitigation and spring yardwork go together and can be scheduled as such. Most often it is the small things that a homeowner attends to that can make a big difference in whether their home will survive during a WUI fire. The following are good examples of small steps that homeowners within the Thompson Nicola Regional District have put in place that make their homes – and subsequently their community – more resilient to wildfire:

## 8.1 Fire-Resistant Roofing

Replacing a roof is one of the single-most expensive FireSmart improvements. The combination of a rate roof that is free of fuel accumulations is a big step to improving the survivability of a home during wildfire event.



*Figure 11 Fire-rated roofing material is proven to be highly resilient against home ignition during a wildfire event. Roof design can also contribute to mitigation of debris accumulation by minimizing valleys and pinch point where debris can be captured*

## 8.2 Landscaping

Simple landscaping changes to one's respective Zone 1 can make all the difference in preventing home ignition. Replacing bark mulch with rock, replacing conifers with deciduous, and utilizing low flammable plants within gardens are all great steps one can make towards increasing their home's resiliency. Maintaining a green lawn is the best standard however, a mowed lawn is still a fire-resistant lawn – grasses shorter than 10cm are less likely to burn intensely. Removal of dead leaves and pine needle litter will also help to reduce fuel sources within the yard.



*Figure 12 This home demonstrates several FireSmart landscaping attributes. The gravel provides a non-combustible surface creating a break from direct flame contact to the home. Conifers have been removed up to 10m away and ladder fuels have been cleared. Leafy, deciduous plants are the preferred vegetation to be found in zone 1.*

## 9.0 Next Steps

After reviewing the contents of this assessment and its recommendations, it is up to the Walhachin community to determine whether or not they will implement the recommendations. The recommendations and FireSmart guidelines noted above are proven and time-tested to be effective in reducing the risk of wildfire losses. It is believed that there is great potential for the community and its residents to work together to reduce the wildfire threat quickly and substantially by acting to mitigate priority issues.

Should the Walhachin community wish to seek FireSmart Community recognition status it is encouraged for them to contact the Local FireSmart Representative and to also create a FireSmart Board. A FireSmart Board is a multi-disciplinary group of volunteer representatives of the neighborhood or community who are responsible for driving the FireSmart initiative in their community and ensuring the recognition criteria are met.

If the report and the recommendations are accepted and recognition will be sought, the Walhachin FireSmart Board will create agreed-upon, area-specific solutions to the FireSmart Community Assessment Report recommendations to prepare a FireSmart Community Plan in cooperation with their Local FireSmart representative and local fire agency personnel who may be acting as advisers.

If Walhachin seeks to achieve the national recognition as a FireSmart Community, the following standards should be incorporated into its FireSmart Community Plan:

WALHACHIN FIRESMART COMMUNITY ASSESSMENT REPORT

- Sponsor a local FireSmart Board that maintains the FireSmart Community program and recognition status
- Continue to work with the Local FireSmart Representative or enlist the assistance of a WUI specialist to complete a FireSmart Community Plan which identifies agree-upon, achievable local solutions
- Invest a minimum of \$2.00 annually per capita in its local FireSmart Events and activities and activities (work done by municipal employees or volunteers\*, using municipal or other equipment, can be included, as can provincial/territorial grants dedicate to that purpose).
- Hold a FireSmart Event (e.g. FireSmart Day) each year that is dedicated to a local FireSmart project.
- Submit an application form or annual renewal application form with supporting information to FireSmart Canada. This application or renewal process documents continuing participation in the FireSmart Communities Program with respect to the above criteria.

\* Volunteer hours are calculated at a rate of \$21 per hour or at the rate of service being voluntarily given

10.0 Signature of Local FireSmart Representative

Signed:	Date signed:	
<i>Brittany Seibert</i>	October 25, 2019	Brittany Seibert, LFR Frontline Operations Group, Ltd. Brittany@frontlineops.ca

## APPENDIX 1: Resources

- FireSmart Canada

<https://www.firesmartcanada.ca>

- FireSmart British Columbia

<https://firesmartbc.ca>

- FireSmart Begins at Home Assessment

<https://firesmartbc.ca/wp-content/uploads/2019/07/FireSmart-Home-Assessment.pdf>

- FireSmart Canada Community Recognition Program (FCCRP)

<https://firesmartbc.ca/resource/how-to-apply-for-the-firesmart-canada-community-recognition-program-fccrp/>

<https://firesmartbc.ca/wp-content/uploads/2019/01/FCCRP-Application-Form-1.pdf>

- FireSmart Guide to Landscaping

<https://www.firesmartcanada.ca/mdocs-posts/firesmart-guide-to-landscaping/>

## APPENDIX 2: Community Wildfire Hazard Assessment form



This Community Wildfire Hazard Assessment form provides a written evaluation of the overall community wildfire hazard – the prevailing condition of structures, adjacent vegetation and other factors affecting the FireSmart status of a small community or neighbourhood. This hazard is based on the **hazard factors** and **FireSmart recommended guidelines** found in **FireSmart: Protecting Your Community from Wildfire** (Partners in Protection, 2003) and will assist the Local FireSmart Representative in preparing the FireSmart Community Assessment Report. **NOTE: Mitigation comments refer to the degree to which the overall community complies or fails to comply with FireSmart recommended guidelines with respect to each hazard factor**

<b>Community Name: Walhachin</b>		<b>Date: (mm/dd/yyyy) September 11, 2019</b>
<b>Assessor Name: Brittany Seibert</b>		<b>Accompanying Community Member(s):</b>
<b>Hazard Factor</b>	<b>Ref</b>	<b>Mitigation Comments</b>
<b>1. Roof Assemblies</b>		
a. Type of roofs ULC rated (metal, tile, asphalt, rated wood shakes) unrated (unrated wood shakes)	2-5 3-21	Mixture of roofing materials used throughout the community including asphalt shingles and metal. All roofs seen were of fire-rated construction
b. Roof cleanliness and condition <i>* Debris accumulation on roofs/in gutters; curled damaged or missing roofing material; or any gaps that will allow ember entry or fire impingement beneath the roof covering</i>	2-6	Roofs appear to be clear of litter, however roof condition is variable. Several roofs seen with aging shingles that have begun to peel or are missing, and growth of organics was also present.
<b>2. Building Exteriors</b>		
<b>2.1 Materials</b>		
a. Siding, deck and eaves	2-7 2-8 2-9	Only one home was seen to have a fire-rated building exterior of stucco. All other homes were of various materials including wood and vinyl. Individual eaves were not seen but is expected due to the age of homes that there are those with open eave designs. Wrap around decks were seen through the community.
b. Window and door glazings (singlepane, sealed doublepane)	2-10	Windows are assumed to be double paned. Some older homes and outbuildings may potentially have single paned glass.

FCCRP COMMUNITY WILDFIRE HAZARD ASSESSMENT FORM

<p>c. Ember Accumulator Features (scarce to abundant)</p> <p><i>* Structural features such as open eaves, gutters, unscreened soffits and vents, roof valleys and unsheathed crawlspaces and under-deck areas</i></p>		<p>All structures have a variety of ember accumulator features including roof shapes, deck configurations, open and unsheathed deck construction and gutters. Wrap around decks and flat top roofs are likely to be the main ember accumulators within the community.</p>
<p>d. Nearby Combustibles – firewood, fences, outbuildings</p>	<p>2-11</p>	<p>Firewood was seen in the community and was stacked within 10m of the home. Most properties were seen with outbuildings or also materials within 10-15m of the home. This included RVs, trailers as well as other building materials, personal items or debris.</p>

FCCRP COMMUNITY WILDFIRE HAZARD ASSESSMENT FORM

Hazard Factor	Ref	Mitigation Comments
<b>3. Vegetation</b>		
<b>3.1 PZ-1: Vegetation - 0 - 10m from structure Page Reference 3-5</b>		
a. Overstory forest vegetation (treated vs. untreated)	2-14	The natural fuel type of the community O1, however non-native plants, trees and shrubs have been planted through the community. Several homes were seen with conifer species within 10m of the home, often in direct contact. Some deciduous overstory was also seen.
b. Ladder fuels (treated vs untreated)	2-17	Ladder fuels include low lying branches of conifer trees as well as several combustible plants seen abutting the home including cedar hedges.
c. Surface fuels -includes landscaping mulches and flammable plants (treated vs untreated)	2-16	Lawns overall appear to be kept at low growth. There is a mixture of natural grasses and landscaped grass within the community.
<b>3.2 PZ-2: Vegetation - 10 - 30m from structures Page Reference 3-9</b>		
a. Forest vegetation (overstory) treated vs untreated	2-14	As with the zone 1, several conifers have been planted within the community. Homes are within 10-30m of each other and therefore these neighboring conifers affect PZ-2
b. Ladder fuels treated vs untreated	2-17	See note above and zone 1
c. Surface fuels treated vs untreated	2-16	See note above and zone 1
<b>3.3 PZ-3: Vegetation - 30 - 100m from structures Page Reference 3-13 Provide mitigation comments on the prevailing PZ3 fuel type</b>		
a. Light fuel -deciduous–grass, shrubs	2-16	The community is surrounded by O1 fuel type to the north, south and east and agricultural land to the west. Wild grass and sage

FCCRP COMMUNITY WILDFIRE HAZARD ASSESSMENT FORM

Hazard Factor	Ref	Mitigation Comments
b. Moderate fuel - mixed wood – light to moderate surface and ladder fuels, shrubs	2-17	Outside of the conifers within the community, there are no natural overstory vegetation within the surrounding fuel type.
c. Heavy fuel - coniferous - moderate to heavy surface and ladder fuels, shrubs	2-14	N/A
d. Logging slash, dead/down fuel accumulations	2-16	N/A
e. Diseased forest – without foliage vs with foliage		N/A
f. Fuel islands within community - treated vs untreated		N/A
<b>4. Topography</b>		
<b>4.1 Slope (within 100m of structures)</b>		
a. Slope - Flat or < 10 %, 10 – 30% or >30%	2-19	15-30+ %
<b>4.2 Buildings setback on slopes &gt;30 %, position on slope Provide mitigation comments on items a – c as applicable</b>		
a. Setback from top of slope > 10m, or bottom of slope – valley bottom. b. Buildings located mid-slope c. Setback from top of slope <10m, or upper slope	2-12	The community is located above a steep slope on a natural bench running west to east. Slope continues behind the community to the south which plateaus again above the community. The edge of slope and homes set back (10-20m) has a road in between

FCCRP COMMUNITY WILDFIRE HAZARD ASSESSMENT FORM

Hazard Factor	Ref	Mitigation Comments
<b>5. Infrastructure - Access / Egress, Roads, Driveways and Signage</b>		
5.1 Access Routes – Road Layout To FireSmart Recommended Guideline?		
a. Single Road or Looped Road	3-28	Single road with a single bridge to cross Thompson River
5.2 Roads- width, grade, curves, bridges and turnarounds		
a. To FireSmart Recommended Guideline?	3-30	N/A
5.4 Fire Service Access / Driveways - Grade, Width/Length, Turnarounds		
a. To FireSmart Recommended Guideline?	3-30	N/A
5.5 Street Signs / House Numbers		
a. To FireSmart Recommended Guideline?	3-30	N/A
<b>6. Fire Suppression - Water Supply, Fire Service, Homeowner Capability</b>		
6.1 Water Supply		
a. Fire Service water supply – hydrants, static source, tender or no water supply	3-32	No hydrants seen within community or other water resources. Use of Thompson Rivers would require high performing pressure pump to move water uphill and likely would require a relay system.
6.2 Fire Service		
a. Fire Service < 10 minutes or > 10 minutes, no fire service	2-25	N/A; BCWS crews located in Kamloops
6.3 Homeowners Suppression Equipment		
a. Shovel, grubbing tool, water supply, sprinklers, roof-top access ladder	3-28	Basic suppression tools such as shovels

Hazard Factor	Ref	Mitigation Comments
---------------	-----	---------------------

FCCRP COMMUNITY WILDFIRE HAZARD ASSESSMENT FORM

7. Fire Ignition and Prevention - Utilities, Chimneys, Burn Barrel / Fire Pit, Ignition Potential		
7.1 Utilities		
a. ToFireSmartRecommended Guideline?	2-24	N/A
7.2 Chimneys, Burn Barrel / Fire Pit		
a. ToFireSmartRecommended Guideline?	2-22	N/A
7.3 Ignition Potential Provide mitigation comments on items a – d as applicable		
a. Topographic features adversely affect fire behaviour b. Elevated probability of human or natural ignitions c. Periodic exposure to extreme fire weather or winds d. Other	2-21	Slope could play a role in home loss as it pertains to fire behaviour. Slope below the community will increase fire behaviour, however set back of homes and buffer zone of the road may allow for fire behaviour to be decreased significantly as it crests the edge. Slope stability post fire may be of concern if in combination with heavy rains. Slope to the south likely to help carry fire away from community. Major railway along the south aspect of the community. Agricultural burning may also be a factor
<b>General Comments</b>  Escape routes a concern for the community.		

FCCRP COMMUNITY WILDFIRE HAZARD ASSESSMENT FORM